

XP-TT424B


Thermal Transfer/ Direct Thermal

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon internal diameter: 12.7mm (0.5")
- Bartender special edition



XP-TT424B

Thermal Transfer/ Direct Thermal



MODEL	XP-TT424B
Printing Method	Thermal Transfer/ Direct Thermal
Resolution	200 DPI
Interface	USB2.0 (Standard)/Bluetooth(Optional)/WIFI(Optional)/SD(Optional)
Real Time Clock	Optional
Max Print Speed	127 mm (5") / s
Max Print Width	108mm (4.25")
Max Print Length	1778mm(70")
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	25.4 mm ~ 115 mm
Media Thickness	0.06 mm ~ 0.18 mm
Media Length	10 mm ~1778 mm
Label Roll Capacity	127 mm (5") external diameter
Ribbon	Max length: 90M; Max roll diameter: 35mm; Internal diameter: 0.5" (12.7mm); Ribbon width: 25.4mm-110mm (1"-4.3")
Memory	8MB Flash Memory 8MB SDRAM Micro SD card reader for Flash memory expansion, up to 4GB
Sensor	Gap sensor Printer Head opened sensor Black mark sensor Ribbon end sensor
Processor	32-bit RISC CPU
Power Supply	Input: AC 100-240V; Output: DC 24V/2.5A
Barcode	1D barcode: 1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D barcode: PDF-417, Maxicode, DataMatrix, QR code
Emulation	TSPL-EZ (EPL, ZPL, DPL)
Dimension	246 x 199 x 168mm (L*W*H)
Weight	1.62kg
Safety Standard	FCC, CE, CB, CCC
Environment	Operation condition: -10 ~ 50 °C (14 ~ 122 °F) , 10 ~ 90% non-condensing Storage condition : -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

