



# Xprinter®

## XP-S200M/S260M/S300M

### Thermal Receipt Printer



- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- Screen can be added (XP-S300M)



# XP-S200M/S260M/S300M

## Thermal Receipt Printer



| MODEL                  | XP-S200M   | XP-S260M       | XP-S300M       |
|------------------------|--|----------------|----------------|
| Printing method        | Direct thermal   |                |                |
| Printing speed         | 200mm/s  | 260mm/s        | 300mm/s        |
| Paper width            | 79.5±0.5mm   |                |                |
| Printable area         | 72mm(adjustable by commands)   |                |                |
| Maximum paper diameter | Φ83 mm   |                |                |
| Paper thickness        | 0.06-0.08mm  |                |                |
| Column capacity        | 576 dots/line 512 dots/line  |                |                |
| Line space             | 3.75mm(Changeable by commands)   |                |                |
| Commands               | Compatible with ESC/POS  |                |                |
| Interface type         | USB+Serial/USB+Lan /<br>USB+Bluetooth/USB+WIFI   | USB+Serial+Lan | USB+Serial+Lan |
| Character size         | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24x24 dots   |                |                |
| Dimension              | 180×140×134.1mm(D×W×H)   |                |                |
| Gross weight           | 0.97 kg  |                |                |
| Bar code               | UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128   |                |                |
| 2-dimension code       | QR CODE / PDF417 (USB+Lan)   |                |                |
| Code page              | PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251) |                |                |
| Cutter                 | Partial  |                |                |
| Cutter life            | 1.5 million cuts   |                |                |
| Print head life        | 100KM  |                |                |
| Input buffer           | 64 Kbytes  |                | 2048 Kbytes    |
| NV Flash               | 256 Kbytes   |                |                |
| Power adaptor          | AC110V/220V, 50~60Hz   |                |                |
| Power source           | DC 24V/2.5A  |                |                |
| Cash drawer output     | DC 24V/1A  |                |                |
| Work environment       | Temperature: 0~45°C, humidity: 10~80RH%  |                |                |
| Storage environment    | Temperature: -10~60°C, humidity: 10~90RH%  |                |                |
| Operating system       | Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux   |                |                |



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

