

Xprinter®

XP-P323B

Mobile Label printer



Key features

- Support direct USB charging;
- Long lasting battery life;
- Dual mode bluetooth;
- OLED screen available;
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-P323B

Mobile Label Printer



Printing	
	XP-P323B
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	Max. 70mm (2.7") / s
Max.print width	72 mm (2.8")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	20 mm ~ 76 mm
Media thickness	0.06 mm ~0.254 mm
Label roll diameter	50mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	Standard version: USB+Bluetooth Optional:USB+WIFI
Screen	OLED (1.3") Resolution:128*64 pix
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code,Aztec
Rotation	0°、 90°、 180°、 270°
Emulation	TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS
Physical Features	
Dimensions	124×108×61mm (D×W×H)
Weight	357 g
Reliability	
Printer head life	30 KM
Software	
Operation system	Windows / Android / iOS
SDK	Windows / Android / iOS
Power supply	
Output	DC 9V/2A
Battery	7.4V/2500mAh
Environmental Conditions	
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

